

## WM1-L Wrapper - Medium Speed



## **Wrapping Machine**

Daky Pack's WM-Series Wrapping Machines are part of the primary section of the production, specifically designed for keeping product integrity and run ed to synchroniz the press.

Production speed: approx. 100 to 120 portion/min.

Paper centering system can be equipped on Daky Pack's WM - Wrappers.

All our machines are provided with:

- Electrical panel in accordance with in force regulations.
- Product Presence control system.
- Automatic oil lubrication of the mechanical equipment inside the machine.
- Inverter controlled main machine driver.
- Touchscreen HMI (Human Machine Interface).
- Speed control.
- Production monitoring.
- All part in contact with product are food grade.
- Safety guards according to CE rules.
- Section for possible assembly of mechanical marking or ink jet or laser printer.










| Technical Data              |                                     |  |  |  |  |  |
|-----------------------------|-------------------------------------|--|--|--|--|--|
| Production Capacity         | 100 ÷ 120 portion/min.              |  |  |  |  |  |
| Installed Power (Kw, V, Hz) | 3Kw - 400V - 50/60Hz                |  |  |  |  |  |
| Compressed Air Consumption  | 20 NI/min (Min. Op. Pressure 6 bar) |  |  |  |  |  |
| Vacuum Pump Flow            |                                     |  |  |  |  |  |
| Weight                      | 2000 kg approx.                     |  |  |  |  |  |

|   |    |   | • |    |   | _ • |   |   |   |
|---|----|---|---|----|---|-----|---|---|---|
| ы | ОХ |   | ш | ne | n | S١  | O | m | Ŀ |
| _ |    | _ | - | _  | ш | ~"  | • | ш | _ |

| A (min.÷max.)   | 30 mm ÷ 50 mm |  |  |
|-----------------|---------------|--|--|
| B (min.÷ max.)  | 30 mm ÷ 70 mm |  |  |
| C (min. ÷ max.) | 18 mm ÷ 29 mm |  |  |
| Weight          | 16 g ÷ 100 g  |  |  |
| Wrapping Style  | Bottom Fold   |  |  |



Sizes out of range can be handled after been evaluated from technical office.

