
UM-F Forming Dosing Wrapping Big Portions - Cheese Solutions



UM-F Forming Dosing Wrapping and Cartoning Machine

UM-F represents a NEW Machine generation in the area of Cheese Portions.

The working process starts with the formation of the wrapping shells from reel-fed sealing aluminum foil for subsequent filling of cheese in the dosing station of the machine.

Production speed: approx. 65 ÷ 80 pcs/min *depending on product quality.

The paper design could be continuous printing or (option) electronically centered with an automatic system coming from the panel. (NO print on the wrapping Film).

An automatic cutting device is foreseen for foil cuts at the proper size, equipped with electrical sensors to control anomalies during the process, e.g. finished foil reel, avoid empty packs, etc.

A single piston device performs the shell forming where the Cheese will be dosed; giving a significant improvement of SIGMA factor. **PATENTED**

UM-HS HIGHLIGHTS:

- Compact footprint.
- Lubrication for life ("dry" machine bottom, means no oil consumption, no risk of stuck in lubrication pipes).
- Modern servo driven doser which significantly reduces the Standard Deviation (big product amount saving).
- Possibility of automatic weight correction (option with a check weigher with TREND correction).
- Double wrapping film holder with semi automatic reel change -splicing (option).
- Bigger reel size, thus guaranting higher rate of efficiency.
- Maintenance friendly (TPM).
- Increased cost saving for maintenance.
- 4.0 Industry compatible (IT connection compatible).









| Technical Data | | |
|-----------------------------|--------------------------------------|--|
| Production Capacity | Up to 105 portions/min. | |
| Installed Power (Kw, V, Hz) | 13Kw - 400V - 50/60Hz | |
| Compressed Air Consumption | 100 NI/min (Min. Op. Pressure 6 bar) | |
| Vacuum Pump Flow | 90 m3/h (Head: 150 mbar) | |
| Weight | 5000 kg approx. | |

| | Portion Dimensions | | |
|----------------|--------------------|------------------------------------|--|
| | Square | Rectangular | |
| A (min.÷max.) | 78 mm max | 110 mm max | |
| B (min.÷max.) | - | 58 mm max | |
| C (min.÷max.) | 39 mm max | 36 mm max | |
| Weight | 100 g ÷ 250 g | 100 g ÷ 250 g | |
| Wrapping Style | Body - Cover; Hec | Body - Cover; Heat sealed wrapping | |





Sizes out of range can be handled after been evaluated from technical office.

